



FPi 2700
An inserting system as variable as your work.



FPi 2700

Versatility in action. Premium package for more power.


If you're looking for an inserting solution with a diverse range of applications for cleverly organising your outgoing mail, the **FPi 2700** inserting system is the perfect choice for your office. Whether mailings with enclosures or single- and multi-page daily mail – the **FPi 2700** will get your individual documents into the mail in no time.

This compact, next-generation system builds on tried-and-tested inserting technology but offers significantly enhanced performance and features.



Enhanced performance? Available whenever you need it: the optional FPi 2700 premium package. A real performance boost for your system. Shift your FPi 2700 to power mode with a special activation code:

- Higher speed: up to 2,500 insertions per hour
- Increased folding capacity: single-fold up to 8 pages
- Increased multi-feed: up to 10 pages + 1 enclosure



► Reliable, versatile, powerful

Feed, collect, fold, insert and seal. Processes up to 2,000 letters per hour in C6, C6/5, DL or C5 size – with or without enclosures (reply cards, flyers, return envelopes).

► Easy to use

Incredibly easy to use thanks to a huge 7" touchscreen and intuitive, graphics-based menu guidance. Recurring jobs can be saved and started at any time.

► Equipped for your needs

Choose from four different equipment levels (1/1.5/2/2.5 stations) for a customised configuration. The top equipment level with 2.5 stations (FPi 2725) allows you to integrate an optional MaxiFeeder for reply envelopes or enclosures, while the FPi 2725 S uses a short special feeder for processing different types of paper (e.g. coated).

Reads all common codes

Barcodes (1D, 2D), OMR – the optional CIS scanner can read all control codes, regardless of their positions.

Folding as set

The **FPi 2700** can collect your documents prior to folding and process up to five sheets as sets with a single, zig-zag or letter fold. You can also use the fold function to create your own flyers.

High-capacity vertical stacker (HCVS)

Can hold up to 500 sealed envelopes.



Versatile read functions

The CIS scanner (optional) can read all different types of control codes across the entire page width and with no adjustments necessary.



Three letter output options

Available as options for any configuration:

- Collection tray (100 letters)
- 02 Side exit (225 letters)
- 03 High-capacity vertical stacker (500 letters)







03

Multi-channel

LAN, Wi-Fi or USB - it's up to you! Load your inserting jobs to your computer quickly and easily using the USB drive.



Daily Mail Function

Document sets containing up to five pages can be fed in by hand. An enclosure can also be added automatically from the feeder.



Feeder swap

Load stations alternately to double capacity and ensure virtually non-stop operation.



Energy-saving



FPi 2700

Technical data



Max. inserting speed per hour, standard/premium	2,000/2,500
Number of feed stations	1–2.5
Touchscreen (size)	7"
Job memory	50
Code reading: OMR, BCR 1D and 2D	optional
Capacity – feed stations Automatic station (80 g/m²)	325
Short feeder (max. number of enclosures)	110
MaxiFeeder – optional for FPi 2725 (max. number of A4 sheets, 80 g	ı/m²) 1,000
Envelopes (C6, C6/5, DL, C5)	150
Capacity – stackers (max. number of envelopes)	
Collection tray	100
Side envelope exit (right/left)	225
High-capacity vertical stacker	500
Folding speed	F (0
Single (A4, 80 g/m²) standard/premium	5/8 pages
Letter fold, Z-fold (A4, 80 g/m²)	5 pages
Set thickness	max. 2 mm
Documents	
Paper sizes	A4, A5, A6
Height	90–356 mm
Width	130–230 mm
Grammage/quality (enclosures)	60–170 (250) g/m ²
Max. filler thickness in mm	2
Dimensions (examples)	
Configuration: 1 station + collection tray Length × height × depth (mm) Weight (kg)	1,360 × 580 × 420 67
Configuration: 2.5 stations + high-capacity vertical stacker Length × height × depth (mm) Weight (kg)	1,360 × 740 × 420 84
Noise emissions	
Single operation, standard/premium	65/66 dB(A)
Operation with high-capacity vertical stacker, standard/premium	67/68 dB(A)

Standard functions

Automatic program, feeder swap, multi-feed (standard up to 3; reading up to 5; premium up to 10 pages), daily mail, collection prior to folding, 'No fold' and 'Fold only', double-sheet control, counting functions

Subject to technical modifications.

© 2024 Francotyp-Postalia. All rights reserved. The FP logo and Francotyp-Postalia product logos are trademarks or registered trademarks of Francotyp-Postalia GmbH.

The right fold turns an ordinary A4 sheet into a small brochure or the perfect mailing.

Choose from all modern fold types used in offices: single fold, zig-zag fold, double parallel fold and letter fold.



Model versions/stations (examples)



FPi 2710

1 automatic station



FPi 2715

- · 1 automatic station
- 1 short feed station for enclosures



FPi 2720

· 2 automatic stations



FPi 2725

- $\cdot \ 2 \ \text{automatic stations}$
- · 1 short feed station for enclosures

FPi 2725 S

- \cdot 2 automatic stations
- · 1 short special feeder

CERTIFIED TO

ISO 9001
ISO 14001
ISO 50001
OHSAS 18001





Francotyp-Postalia Ltd.
74 Questor, Powdermill Lane
Dartford, Kent DA1 1EF
01322 424890
www.fpmailing.co.uk

